

# Specifikációk

## Wind-Free™ Elite



Indoor Unit		AR09TXCAAWKNEU	AR12TXCAAWKNEU		
Outdoor Unit		AR09TXCAAWKXEU	AR12TXCAAWKXEU		
Capacity	Capacity (kW)	Cooling	2.50	3.50	
		Heating	3.20	4.00	
	Cooling (Min - Max)	Cooling (Min - Max)	0.9 - 3.6	0.9 - 4.8	
		Heating (Min - Max)	0.8 - 7.1	0.8 - 7.3	
	EER/COP (W/W)	EER (Cooling)	4.63	3.95	
		COP (Heating)	4.74	4.26	
	SEER/SCOP (W/W)	SEER (Cooling)	8.80	8.50	
		SCOP (Heating)	5.10	5.10	
	Energy Grade	Star/Ticks/Level	A+++/A+++	A+++/A+++	
	Air Circulation (Max, m <sup>3</sup> /min)		11.1	12.1	
	Moisture Removal (l/hr)		1.00	1.5	
	Noise Level Power	Catalogue	Indoor High/Low	56	58
			Outdoor High	59	62
	Noise Level Pressure	Catalogue	Indoor High/Low	39 / 16	40 / 16
Outdoor High			45	46	
Electrical Data	Energy Efficiency	Operating Current (Cooling)	2.9	4.1	
		Operating Current (Heating)	3.4	4.4	
	Power Source	Power Consumption (Cooling)	540	885	
		Power Consumption (Heating)	675	940	
Physical Specification	Dimension	Net Dimension Indoor	889x299x215	889x299x215	
		Net Dimension Outdoor	790x548x285	790x548x285	
		Gross Dimension Indoor	950x290x375	950x290x375	
		Gross Dimension Outdoor	913x622x371	913x622x371	
	Weight(kg)	Net Weight Indoor	10.6	10.6	
		Net Weight Outdoor	32.5	32.5	
		Gross Weight Indoor	12.7	12.7	
		Gross Weight Outdoor	34.8	34.8	
	Loading Q'ty	W Pipe	Set (20/40ft/40ft HC)	-	-
			Set (20/40ft/40ft HC)	85 / 180 / 208	85 / 180 / 208
W/O Pipe		Indoor (20/40ft/40ft HC)	288 / 592 / 660	288 / 592 / 660	
		Outdoor (20/40ft/40ft HC)	111 / 234 / 312	111 / 234 / 312	
Technical Information	Piping Length	Piping Length (Max, m)	15	15	
		Piping Height	8	8	
	Refrigerant	Type	R32	R32	
		Charging (kg)	0.965	0.965	
		Charging (tCO <sub>2</sub> e)	0.65	0.65	
	SVC Valve	Liquid (OD)	6.35	6.35	
Gas (OD)		9.52	9.52		

# Specifikációk

## Wind-Free™ Elite



Indoor Unit		AR09TXCAAWKNEU	AR12TXCAAWKNEU	
Outdoor Unit		AR09TXCAAWKXEU	AR12TXCAAWKXEU	
General Feature	Air Flow	Wind-Free	•	•
		Air Direction Control (Up/Down)	Auto	Auto
		Air Direction Control (Left/Right)	Auto	Auto
		Air Flow Control Step (Cool/Fan)	5/4	5/4
		Auto Fan speed	•	•
	Air Purification	Easy Filter Plus	•	•
		Tri-care Filter	•	•
		Auto Clean (Self Cleaning)	•	•
	Convenience	Smart Things	•	•
		MDS (Motion Detect Sensor)	•	•
		Filter Cleaning Indicator	•	•
		Indoor Temp. Display	•	•
		Remote Controller	•	•
		Display On/Off 88 Display	•	•
		Beep On/Off	•	•
		24-Hour Timer / Real Timer	24 Hr	24 Hr
		Auto Changeover	•	•
		Auto Restart	•	•
	Low Ambient	Condition	T1	T1
		Cooling (°C)	-10~46	-10~46
Heating (°C)		-15~24	-15~24	
Operating Mode	Comfort	AI AUTO & WIFI & MDS	•	•
		AI AUTO & Auto Mode	NO	NO
		Fast Cool	•	•
		Good Sleep	•	•
	Eco mode	•	•	
	Dehumidification	•	•	
	Fan Mode	•	•	
	Quiet	•	•	
	Outdoor Unit & PBA	Compressor Type	BLDC	BLDC
		Triple Protector	•	•
Anti-Corrosion Fin Compressor PBA Protector		•	•	
Window Display	DISPLAY TYPE	88	88	
	LED Spec	LED 3ea	NO	NO
		AI/Timer/WIFI	•	•
		Saving/Timer	NO	NO
		Operating/Saving	NO	NO
MDS	MDS Icon	•	•	